



● Features


- 2 Mounting Option
 - WYF****D : Din Rail Mounting
 - WYF**** : Screw Mounting
- Wide Band : High Attenuation
- Band Width : 150KHz~30MHz
- Low Leakage
- RoHS Compliant
- KC(안전인증) Approved by HH03009-15004A
- Inverter Output Type : Model Type"C"
(WYFT05T1C)

● Specifications


ITEM	MODEL	SYMBOL	WYFT05T1A(D)	WYFT10T1A(D)	WYFT15T1A(D)	WYFT20T1A(D)	WYFT30T1A(D)
			WYFT05T1C(D)	WYFT10T1C(D)	WYFT15T1C(D)	WYFT20T1C(D)	WYFT30T1C(D)
Rated Voltage	V		250				
Rated Current	A		5	10	15	20	30
Frequency	Hz		50/60				
Dielectric Withstand	V		2000Vac for 1 minute or 1075Vdc for 1 minute				
Insulation Resistance	MΩ		500				
Leakage Current	mA		≤2,5mA at the 250Vac				
Operating Temperature	°C		-25°C ~ +100°C [Refer to Derating Curve TYPE-2]				
Operating Humidity	RH		35~85%RH				
Weight	kg		0,5				

※ "D" : DIN-Rail type of page 184, "C" : Inverter Output Type / Derating Curve of page 103


● Circuit Diagram





● Terminal











● Characteristics



● Dimension



● Characteristics



※ CM : Common mode, DM : Differential mode