


단상 복권형으로 입력 AC380/440V 출력 AC 220V로 Lead-Wire로 제작되었으며 권선 보호 덮개형으로 분진, 습기가 많은 곳에서 사용하도록 제작하였습니다.

Input voltage of single phase is AC 380V/440V and output is AC 220V. It has been with drawn by lead wire and manufactured to be used at the place of severe dust and humidity and vibration etc.



•Circuit Diagram



● Specifications

Insulation Class B

MODEL NO.	TYPE	SPECIFICATIONS		VA	DIMENSIONS (mm)						SUITABLE WIRE		WEIGHT (kg)
		PRI.(V)	SEC.(V)		W	H	D	b	d	Ø2	PRI.	SEC.	
WY42-40DE	WE	0-380-440 흑(BLACK) 청(BLUE) 황(YELLOW)	0-220 흑(BLACK) 적(RED)	40	78	68	81	64	54	4 x 11	0.75mm ²	0.75mm ²	1.30
WY42-60DE				60	78	68	86	64	59	4 x 11			1.60
WY42-80DE				80	89	75	101	76.5	67.5	5 x 14			1.95
WY42-100DE				100	99	85	103	79	70	5 x 14			2.27
WY42-150DE				150	99	85	113	79	80	5 x 15			3.20

● Dimension

• WP Type

