

# REACTOR


## DC Reactor



### ● Specification

- Rating : DC 380/440V
- Dielectric withstand : AC 3000V / 1min
- Insulation resistance : 100 M.Ω 이상, DC 500V / 100M.Ω
- IP Class : IP20
- Sound level : Less than 65db
- Operating temp. : -20℃ ~ +40℃

### ● Circuit Diagram



### ● DC 380/440V (Impedance Voltage : 5.5Vac)

MODEL	용량(KW)	정격전류 (A)	Dimensions(mm)							TYPE	Weight (kg)
			W	D	H	W1	D1	øE	øF		
WYDCL4-0.75	0.75	1.7	78	87	96	57	67	5	M4	A	1.5
WYDCL4-1.5	1.5	3.4	78	87	96	57	67	5	M4		2.2
WYDCL4-2.2	2.2	7.5	88	104	108	63	87	5	M4		3.1
WYDCL4-3.7	3.7	10	88	104	108	63	87	5	M4		4.2
WYDCL4-5.5	5.5	15	99	113	110	72	91	6	M4		5.9
WYDCL4-7.5	7.5	20	110	110	121	76	93	5.5	M4		7.2
WYDCL4-11	11	30	120	128	125	84	105	5.5	7		9
WYDCL4-15	15	38	140	144	131	98	111	6	9	11	
WYDCL4-18.5	18.5	50	140	144	136	98	116	6	9	13	
WYDCL4-22	22	58	140	144	136	98	116	6	9	14	
WYDCL4-30	30	67	160	167	146	114	124	6	9	18	
WYDCL4-37	37	82	160	167	146	114	124	6	9	18	
WYDCL4-45	45	100	160	167	156	114	134	6	9	19	
WYDCL4-55	55	121	184	191	192	134	133	7	9	22	
WYDCL4-75	75	167	184	191	192	134	133	7	9	25	
WYDCL4-90	90	201	184	191	192	134	133	7	9	28	
WYDCL4-110	110	245	184	191	192	134	133	7	9	32	
WYDCL4-132	132	290	220	190	245	120	158	10	9	34	
WYDCL4-160	160	357	219	230	230	120/180	160	10	9	40	
WYDCL4-185	185	420	220	190	245	120	158	10	13	57	
WYDCL4-220	220	500	245	238	265	180	207	8.5	13	68	

### ● Dimension

