


단상 단권형으로 입력 AC 220V 출력 AC 110V로 Lead-Wire로 제작되었으며 권선보호형 덮개 Type으로 분진, 습기가 많은 곳에서 사용하도록 제작하였습니다.

Manufactured by lead wire, it is a single phase auto transformer with AC220V of input and AC110V of output. It can be used at the severe place of dust, vibration and humidity by protective cover of winding.



•Circuit Diagram



● Specifications

Insulation Class B

MODEL NO.	TYPE	SPECIFICATIONS		VA	DIMENSIONS (mm)						SUITABLE WIRE		WEIGHT (kg)
		PRI.(V)	SEC.(V)		W	H	D	b	d	Ø2	PRI.	SEC.	
WYAU-75DE	WE	O-220 흑(BLACK) 적(REL)	O-110 흑(BLACK) 갈(BROWN)	75	78	68	81	64	54	4 x 11	0.75mm ²	0.75mm ²	1.30
WYAU-100DE				100	78	68	86	64	59	4 x 11			1.60
WYAU-150DE				150	89	75	101	76.5	67.5	5 x 14			1.95
WYAU-200DE				200	99	85	103	79	70	5 x 14			2.27
WYAU-300DE				300	99	85	113	79	80	5 x 15			3.20

● Dimension

- WP Type

