




• Circuit Diagram



### Specifications

Insulation Class B




| MODEL NO.     | TYPE | SPECIFICATIONS        |                   | VA   | A   | DIMENSIONS (mm) |       |     |     |       |       |     |    |         |        |      |       | WEIGHT (kg) |
|---------------|------|-----------------------|-------------------|------|-----|-----------------|-------|-----|-----|-------|-------|-----|----|---------|--------|------|-------|-------------|
|               |      | PRI.(V)               | SEC.(V)           |      |     | W               | H     | D   | a   | b     | c     | d   | e  | (a.c)Ø1 | Ø2     | M    |       |             |
| • 32V SERIES  |      |                       |                   |      |     |                 |       |     |     |       |       |     |    |         |        |      |       |             |
| WYTB-3240AP   | WT   | 0-110-200<br>-220-(E) | 0-26-28<br>-30-32 | 40   | 1.2 | 79              | 89    | 83  | 42  | 57    | 48.5  | 63  | 7  | Ø3.6    | 5 x 12 | M3.5 | 1.31  |             |
| WYTB-3260AP   |      |                       |                   | 60   | 1.8 | 79              | 89    | 88  | 42  | 57    | 53.5  | 68  | 7  | Ø3.6    | 5 x 12 | M3.5 | 1.65  |             |
| WYTB-3280AP   |      |                       |                   | 80   | 2.5 | 89              | 98    | 105 | 46  | 65    | 62    | 83  | 7  | Ø3.6    | 5 x 12 | M3.5 | 2.30  |             |
| WYTB-32100AP  |      |                       |                   | 100  | 3   | 98              | 106   | 105 | 54  | 72    | 61    | 88  | 7  | Ø3.6    | 6 x 12 | M3.5 | 2.59  |             |
| WYTB-32150AP  |      |                       |                   | 150  | 6   | 112             | 106   | 105 | 58  | 76    | 60    | 82  | 10 | Ø3.6    | 5 x 10 | M4   | 3.45  |             |
| WYTB-32200AP  |      |                       |                   | 200  | 6   | 112             | 114   | 110 | 58  | 76    | 65.5  | 88  | 10 | Ø3.6    | 5 x 10 | M4   | 3.60  |             |
| WYTB-32300AP  |      |                       |                   | 300  | 9   | 121             | 122   | 114 | 66  | 84    | 73    | 95  | 10 | Ø3.6    | 5 x 10 | M4   | 4.97  |             |
| WYTB-32500AP  |      |                       |                   | 500  | 15  | 140             | 140   | 126 | 82  | 98    | 79.5  | 105 | 10 | Ø3.6    | 6 x 12 | M4   | 7.10  |             |
| WYTB-32750AP  |      |                       |                   | 750  | 23  | 160             | 162   | 146 | 96  | 114   | 92.5  | 125 | 10 | Ø3.6    | 6 x 13 | M4   | 10.70 |             |
| WYTB-321KAP   |      |                       |                   | 1K   | 30  | 160             | 160   | 157 | 96  | 114   | 102.5 | 135 | 10 | Ø3.6    | 6 x 14 | M4   | 12.30 |             |
| WYTB-321.5KAP |      |                       |                   | 1.5K | 60  | 184             | 188.5 | 150 | 110 | 133.8 | 95.2  | 122 | 16 | Ø3.6    | 7 x 14 | M6   | 17.00 |             |
| WYTB-322KAP   |      |                       |                   | 2K   | 80  | 184             | 188.5 | 170 | 110 | 133.8 | 115.2 | 137 | 16 | Ø3.6    | 7 x 19 | M6   | 20.10 |             |

※ 정격용량 : 최대전압(TAP)에서의 용량임.

※ Rated capacity : Capacity at the maximum voltage(TAP).

### Dimension

#### • WT Type



### Terminal



40VA~100VA : Max 6, Min 3.5  
150VA~1kVA : Max 9, Min 4  
1.5~2kVA : Max 15, Min 6