


## WYEW-AP/HP Series (복권)



단상 복권형으로 입력은 AC220, 380/440V이며 출력은 AC24V로 Lead-Wire 및 권선보호형 카바 사용으로 분진이 많이 발생하는 곳이나 습기가 많은 곳에서 사용하기 용이 하도록 설계된 제품입니다.

Input voltage of single phase is AC 220, 380/440V and output is AC24V The product has been designed to use easily in the place of dust and humidity with lead wire and cover to protect winding.

• Circuit Diagram



● Specifications

MODEL NO.	TYPE	SPECIFICATIONS		VA	DIMENSIONS (m/m)						SUITABLE WIRE		WEIGHT (Kg)
		PRI.(V)	SEC.(V)		W	H	D	b	d	Ø2	PRIMARY	SECONDARY	
• 24V SERIES													
WYEW-40AP	WE	0-220	0-24	40	78	68	81	64	54	4 X 11	0.75mm <sup>2</sup>	0.75mm <sup>2</sup>	1.30
WYEW-60AP				60	78	68	86	64	59	5 X 14		0.75mm <sup>2</sup>	1.46
WYEW-80AP				80	89	75	101	76,5	67,5	5 X 14		0.75mm <sup>2</sup>	1.95
WYEW-100AP		흑(BLACK)	흑(BLACK)	100	99	85	103	79	70	5 X 15		0.75mm <sup>2</sup>	2.27
WYEW-150AP		적(RE D)	적(RE D)	150	99	85	113	79	80	5 X 15		1.25mm <sup>2</sup>	2.84
WYEW-200AP		200	108	90	110	90	80	5 X 12	1.25mm <sup>2</sup>	3.45			
WYEW-300AP		300	118	99	115	102	78	5 X 12	2.00mm <sup>2</sup>	4.78			
WYEW-500AP		500	137	115	119	116	81	5 X 12	3.50mm <sup>2</sup>	6.89			
WYEW-HP40AP		WE	0-380,440	0-24	40	78	68	81	64	54		4 X 11	0.75mm <sup>2</sup>
WYEW-HP60AP	60				78	68	86	64	59	5 X 14	0.75mm <sup>2</sup>	1.46	
WYEW-HP80AP	80				89	75	101	76,5	67,5	5 X 14	0.75mm <sup>2</sup>	1.95	
WYEW-HP100AP	흑(BLACK)		흑(BLACK)	100	99	85	103	79	70	5 X 15	0.75mm <sup>2</sup>	2.27	
WYEW-HP150AP	갈(BROWN)		백(WHITE)	150	99	85	113	79	80	5 X 15	1.25mm <sup>2</sup>	2.84	
WYEW-HP200AP	200		108	90	110	90	80	5 X 12	1.25mm <sup>2</sup>	3.45			
WYEW-HP300AP	적(RE D)		적(RE D)	300	118	99	115	102	78	5 X 12	2.00mm <sup>2</sup>	4.78	
WYEW-HP500AP	500		137	115	119	116	81	5 X 12	3.50mm <sup>2</sup>	6.89			

● Dimension

• WP Type

