

WY42-DE Series (복권)




단상 복권형으로 입력 AC380/440V 출력 AC 220V로 Lead-Wire로 제작되었으며 권선 보호 덮개형으로 분진, 습기가 많은 곳에서 사용하도록 제작 하였습니다.

Input voltage of single phase is AC 380V/440V and output is AC 220V. It has been with drawn by lead wire and manufactured to be used at the place of severe dust and humidity and vibration etc.



• Circuit Diagram



● Specifications

MODEL NO.	TYPE	SPECIFICATIONS		VA	DIMENSIONS (m/m)						SUITABLE WIRE		WEIGHT (kg)
		PRI. (V)	SEC.(V)		W	H	D	b	d	Ø2	PRI.	SEC.	
WY42 - 40DE	WE	0-380-440 흑청황 (BL) (BLUE) (YE)	0-220 흑적 (BL) (RED)	40	78	68	81	64	54	4 X 11	0.75mm ²	0.75mm ²	1.30
WY42 - 60DE				60	78	68	91	64	64	4 X 11			1.60
WY42 - 80DE				80	89	75	101	76.5	67.5	5 X 14			1.95
WY42 - 100DE				100	89	75	103	76.5	73	5 X 14			2.27
WY42 - 150DE				150	99	85	113	79	80	5 X 15			3.20

● Dimension

• WP Type

